

Bath Potters' Supplies

MATERIAL SAFETY DATA SHEET

1. Identification of the preparation/Supplier reference

Trade Name **B116 Turquoise blue.**
Chemical name Zircon vanadium blue.
Synonyms None
Supplier Bath Potters Supplies, Unit 18, Fourth Avenue, Westfield Trading Estate,
Radstock, Nr. Bath. BA3 4XE
Emergency numbers Tel: 01761 411077
E-mail: sales@bathpotters.co.uk

2. Composition

Component	CAS EINECS	% of composition
C.I.Pigment Blue 71	68186-95-8	100

3. Health Hazard Identification

Inhalation Excessive exposure may cause symptoms of chronic lung disease.
Ingestion The product is of low solubility in body fluids and it is likely to be of low acute toxicity.
Eyes May cause physical irritation and inflammation.
Skin The material is not a primary irritant, but as with any abrasive powder it may give rise to minor irritation.
Some cobalt compounds have been known to produce dermatitis and sensitisation.

4. First Aid Measures

Inhalation Remove patient to fresh air, loosen tight clothing and seek medical attention.
Ingestion Do not induce vomiting, seek medical advice.
Eyes Wash immediately with copious amounts of water. Seek medical attention if irritation persists.
Skin Wash affected areas with water. If irritation persists, seek medical attention

5. Fire Fighting Measures

Extinguishing Media Suitable for surrounding fire conditions.
Standard fire fighting techniques only are required, i.e. water, sand, carbon dioxide,
chemical foam extinguishers etc.
Special Exposure hazard In the event of a fire, the product may emit harmful or toxic fumes.
Protective equipment Self contained breathing apparatus.

6. Accidental Release Measures

Leaks & Spills Remove any dry materials either by a vacuum cleaner fitted with an efficient filter or by
wet sweeping to avoid dust. Store collected waste in a suitable container before disposal.
Protective equipment Respiratory protective equipment.

7. Handling & Storage

Handling Do not eat, drink, or smoke in areas where the material is used. Wash thoroughly after handling the
material
Local exhaust ventilation is recommended to comply with occupational exposure limits (refer to
Guidance Note EH40 - latest edition)
Storage Store in dry area.

8. Exposure Control/Personal protective Equipment

Engineering controls	Adequate ventilation should be provided so that Occupational Exposure Limits are not exceeded. Local Exhaust Ventilation is normally recommended
Personal protective equipment	Where LEV is not practicable and exposure is likely to be excessive, approved respiratory protection to CEN standards pr EN 140, 141, 143 or 149 should be worn. Protective gloves and overalls are recommended for prolonged contact.

9. Physical & Chemical properties

Appearance & Odour	Blue powder, odourless
Flash point (°C)	Not applicable
Flammability	Inflammable
Explosive properties	Non-explosive
Oxidising properties	None
Specific gravity	Not applicable
Solubility	Insoluble
Melting point (°C)	Not available

10. Stability & Reactivity

Chemical stability	The material is stable
Conditions/materials to avoid	None known
Hazardous decomposition products	None known
Hazardous polymerisation products	None

11. Toxicology Information

Acute toxicology	Likely to be of low toxicity.
Health effects	None known.

12. Ecological information

Ecotoxicity	Not known.
Persistence	Not known

13. Disposal

Dispose in accordance with current waste Disposal regulations (for UK - Control of Pollution (Special Waste) Regulations 1980). Landfill is the most appropriate method.

14. Transport Information

UN/SI No.		Not classified
UN Class		Not classified
Packing group		Not classified
Road	UK	Not classified
ADR		Not classified
Sea	IMO	Not classified
Air	ICAO	Not classified

15. Regulatory information

EC Supply Labelling Harmful X_n
R-Phrases R20/22 Harmful by inhalation and if swallowed.
R33 Danger of cumulative effects.
S-Phrases S13 Keep away from food, drink and animal feeding stuffs.
S20/21 When using do not eat, drink or smoke.
S28 After contact with skin, wash immediately with plenty of soap and water.

UK Occupational exposure limits*	Mg/m ³ 8 hr TWA	% in product
Barium compounds (as Ba)	0.5	1.5

* refer to HSE Guidance note EH40

In accordance with the H.S.E. Approved Code of Practice for CHIP, the recipient is reminded of their obligations under both the Health and Safety at Work Act (HSWA) and the Control of Substances Hazardous to Health Regulations (COSHH), and that the information in any safety data sheet does not constitute the user's assessment of workplace risk.

16. Other information

General industrial hygiene practices are recommended when handling and using this product.

COSHH ACOP: H.S.C. Approved Code of Practice for the Control of Substances Hazardous to Health Regulations 1994.
CHIP 96: Chemicals (Hazard Information and Packaging for Supply) Regulations 1996.
CHIP SDS ACOP: H.S.C. Approved Code of Practice for Safety Data Sheets in accordance with regulation 6 of the CHIP regulations.
HSE EH40: HSE Guidance note EH40 on Occupational Exposure Limits, to be used in conjunction with the COSHH regulations.

The information contained in this safety data sheet has been prepared using the best available information. However, in view of technical developments this may alter.

The material must only be used for its stated purpose and the information contained within this data sheet is offered solely for use in the evaluation of this product in respect of safety, health and environmental hazards.

Due to the many factors outside our control when using this product we cannot accept liability for any injury, accident, loss or damage caused through its use.

24.08.21