

White Earthenware Clay

Name	Brief Description	Temperature	Price per bag (12.5kg unless otherwise stated)
VBP1 Low-fire Smooth	Suitable for throwing, machine making and slab building	1060 - 1160°C	£8.76
VBP2 Grogged	Addition of white grog increasing resistance to cracking and warping.	1080 - 1180°C	£10.60
VBP3 Standard Smooth	Suitable for once-firing	1080 - 1180°C	£8.76
PF580	Superwhite Earthenware, an earthenware which throws as well as the best stoneware clays. A blend of carefully graded ball clays gives this clay body outstanding plasticity and strength. Being smooth, strong and very plastic PF 580 is ideal for all production techniques including throwing, pressing and jigger and jollying.	1080 - 1180°C	£11.80
CWE Smooth Throwing Clay	Superb throwing capabilities and is suitable for slab building.	1060 - 1160°C	£7.51
LTW	Suitable for throwing, machine-making and casting. Designed to give a good glaze fit with earthenware glazes. Smooth Texture.	1060 - 1150°C	£12.18
LT25 1141	A very plastic white Earthenware body which throws easily on the wheel.	1100 - 1200°C	£15.55
1141/30	Exceptional handling properties arising from the inclusion of white sand/grog into the plastic LT25 base. Throws well and suitable for larger pots also. Medium Texture.	1100 - 1240°C	£17.05
Paperclay E/S400 T.S. Flax	Smooth body.	1080 - 1200°C	£11.08 (5kg bag)